



# H<sub>2</sub>O Guard<sup>™</sup> - C1000-MCB Microban<sup>®</sup> CARBON BLOCK

Counter Top Water Filtration System

#### H<sub>2</sub>O Guard™ Water Filtration Systems

are high performance water filtration systems designed to substantially improve the quality of your drinking water. They provide great tasting water while producing water that is cleaner, healthier and safer. We strive to provide top quality products and understand that transforming your water from questionable to premiere quality is really not a matter of chance, it's simply a matter of choice.

#### H<sub>2</sub>O Guard™ Water Filtration Systems

The  $H_2O$  Guard<sup>TM</sup> Total Care Water Filtration Systems are designed to address a broad range of issues relating to your drinking water, including items of health concern that are important to your family's health and wellbeing.

**The H<sub>2</sub>O Guard™ C1000-MCB** incorporates a multistage water filtration cartridge designed to provide you with cleaner, clearer, safer, healthier drinking water. One cartridge provides 800 gallons of premium quality drinking water!

### Stage 1 -

 $\rm H_2O$  Guard's Radial Flow Filtration allows water to enter the cartridge through the radius of the filter. This allows the Stage 1 outer layer to trap and retain larger particles such as dirt, rust and sediment. The FDA CFR 21 compliant fine web polypropylene fibers do not impart color, odor or chemicals into the water and are an ideal pre-filtration media.

#### Stage 2 -

Water passes through the NSF Certified Coconut Shell Solid Carbon Block filter to reduce items of health concern. The 0.5 micron carbon block pores micro-strain the water to reduce (through mechanical filtration) substances in your water that are 0.5 micron in size or larger. The 0.5 micron pores also aid to increase the systems adsorptive properties. This allows water to have a longer contact time with the carbon wall and permits the efficient reduction of Volatile Organic Compounds (VOC's – Organic Chemicals), PCB, Pesticides, Herbicides, Chloroform and other chlorination by-products.

H2O GUARD™IS A TRADEMARK OF H2O INTERNATIONAL INC.
3001 S.W. 15th Street Suite C, Deerfield Beach FL 33442 USA

# H<sub>2</sub>O Guard™ - C1000-MCB Microban® CARBON BLOCK

Counter Top Water Filtration System



### The H<sub>2</sub>O Guard™ C1000-MCB also incorporates

throughout the solid carbon filter Microban® technology. Microban® antimicrobial technology inhibits the growth of bacteria that can cause odors and fouling of the filter surface, so your filter keeps working at peak performance. On an unprotected surface, bacteria can double in number every 20 minutes causing premature fouling of the water filter. Microban® antimicrobial product protection works continuously to inhibit the growth of bacteria that can adversely affect filter performance.

## H<sub>2</sub>O GUARD™ **Cartridge Replacement Indicator (CRI)**

## The H<sub>2</sub>O Guard™ Cartridge Replacement

**Indicator (CRI)** is another way H2O Guard<sup>™</sup> helps you safeguard your drinking water. The CRI measures time and informs you when it's time to change your filter. This is an added convenience which takes away the guess work and helps ensure your drinking water system is working at optimal performance. Two LED lights update you on the systems operation. The YELLOW LED indicates less than 10% of filter capacity remains (it's time to order a replacement cartridge), and the **RED LED** indicates the filter capacity has been reached, and it's time to install new cartridge.

Peace of mind made easy!

#### **PRODUCT BENEFITS**

- ✓ Excellent Contaminant Reduction\*\*
- ✓ Superior Taste, Odor and Chlorine Reduction\*\*
- √ 800 Gallon Capacity\*\*
- ✓ Cartridge Replacement Indicator (CRI)
- ✓ VOC, Pesticide, Herbicide Reduction\*\*
- ✓ Carbon Block Certified by NSF®
- ✓ Quick & Easy Install
- ✓ Microban® Antimicrobial Technology

#### **PRODUCT SPECIFICATIONS**

800 gallons (3028 L) **Rated Capacity:** 

**Micron Rating:** 0.5μ **Replacement Filter:** H2OG-MCB

Flow Rate: .75 GPM (2.84 LPM)

@ 60psi

**Maximum Working Pressure:** 100 psig (689.5 kPa) **Minimum Working Pressure:** 30 psig (206.8 kPa) Maximum Operating Temperature: 100 °F (38 °C) Minimum Operating Temperature: 34 °F (1 °C)

#### **COLORS AVAILABLE**







NOTICE: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

\* NSF Standard 53 Certification Pending.

\*\* This water filtration device has not finalized certification with NSF International and has not been approved by the California Water Resource Control Board, therefore, it is not available for sale in the State of California for the contaminant reduction claims listed.

