

H₂O Guard™ - U3000-GAC/KDF Chloramine Removal

Under Counter Water Filtration System

H₂O Guard™ Water Filtration Systems are high performance water filtration systems designed to substantially improve the quality of your drinking water. They provide great tasting water while producing water that is cleaner, healthier and safer. The H₂O Guard™ U3000 is designed to address a broad range of issues relating to your drinking water like taste, odor, chlorine and most importantly, items of health concern that maybe present in your drinking water.

The H₂O Guard™ U3000-GAC/KDF incorporates a three multi-stage water filtration cartridge designed to provide 800-1000 gallons of premium quality drinking water that combine enhanced proven filtration technologies to provide you premier quality drinking water

CARTRIDGE 1 - H2OG-SED5

The H2OG-SED5 pre-filter is a specially manufactured high performance sediment filter designed for high dirt holding capacity and the reduction of fine sediment and rust particles. Its micro-fine web design traps more particles and helps keep other filters in the filtration system working at optimal performance.

CARTRIDGE 2 - H2OG-GAC/KDF 85

The H2O GAC/KDF 85 filter uses an advanced proprietary replaceable cartridge with a granular catalytic coconut shell carbon (GCAC) and KDF 85 process media to remove chloramine, chlorine, organic volatile compounds (VOC) and other contaminants responsible for taste, appearance and odor that may be present in municipally supplied water.

CARTRIDGE 3 -H2OG-CB5P

The final stage is the exclusive H₂O Guard H2OG-CB5P filter which has been specially designed with premium Coconut shell carbon as a final Polishing cartridge to improve taste and render a pleasant bottled water like taste to your drinking water.



H₂O GUARD™ IS A TRADEMARK OF H₂O INTERNATIONAL INC.
3001 S.W. 15th Street Suite C, Deerfield Beach FL 33442 USA

H₂O Guard™ - U3000-GAC/KDF Chloramine Removal Under Counter Water Filtration System



PRODUCT BENEFITS

- ✓ 5μ Filtration
- ✓ Superior Taste and Odor
- ✓ Lead and VOC Reduction
- ✓ 800 Gallon Capacity
- ✓ Chloramine and Chlorine Removal
- ✓ Carbon Block, GAC/KDF 85 Cartridge Certified by NSF®
- ✓ Quick & Easy Install and Replace

PRODUCT SPECIFICATIONS

Rated Capacity:	800 gallons (3785.41 L)
Micron Rating:	5μ
Replacement Filter:	H2OG-SED5 H2OG-GACKDF H2OG-CB5P
Flow Rate:	.75 GPM (2.84 LPM) @ 60 psi
Maximum Working Pressure:	100 psig (689.5 kPa)
Minimum Working Pressure:	30 psig (206.8 kPa)
Maximum Operating Temperature:	100 °F (38 °C)
Minimum Operating Temperature:	34 °F (1 °C)

NOTICE: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

** NSF Standard 53 Certification Pending.*

*** This water filtration device has not finalized certification with NSF International and has not been approved by the California Water Resource Control Board, therefore, it is not available for sale in the State of California for the contaminant reduction claims listed.*



H₂O GUARD™
SAFE AND CLEAN WATER SOLUTIONS

H2O GUARD™ IS A TRADEMARK OF H2O INTERNATIONAL INC.
3001 S.W. 15th Street Suite C, Deerfield Beach FL 33442 USA